

STANDARDNÍ NÝTY



Zapuštěná hlava 120°

OCEL/OCEL



TĚLO: Pozinkovaná ocel A3K

TRN: Pozinkovaná ocel A1K



UNE - EN ISO 15980

Testováno dle EN ISO 14589

d1 Ø mm	L Nominální mm		d2 Ø mm	K mm	W Ø mm	BALENÍ					Kód zboží	
		mm				 vnitřní	 veknovní	MIN. mm	MÁX. mm	(N)	(N)	
3,2	6	3,30	6,30	1,00	2,00	500	4.000	1,5 - 3,5		1100	1200	01220003206
	8					500	4.000	3,5 - 5,5				01220003208
	10					500	4.000	5,5 - 7,0				01220003210
	12					500	4.000	7,0 - 9,0				01220003212
4,0	6	4,10	7,60	1,30	2,40	500	4.000	2,0 - 3,0		1700	2200	01220004006
	8					500	4.000	3,0 - 5,0				01220004008
	10					500	4.000	5,0 - 6,5				01220004010
	12					500	3.000	6,5 - 8,0				01220004012
	14					500	3.000	8,0 - 10,0				01220004014
4,8	8	4,90	9,50	1,40	2,93	500	3.000	2,5 - 4,0		2900	3100	01220004808
	10					500	3.000	4,0 - 6,0				01220004810
	12					250	2.000	6,0 - 8,0				01220004812
	14					250	2.000	8,0 - 10,0				01220004814
	16					250	2.000	10,0 - 11,0				01220004816
	18					250	1.500	11,0 - 13,0				01220004818
	20					250	1.500	13,0 - 15,0				01220004820
5,0	12	5,10	9,50	1,60	2,93	250	2.000	6,0 - 8,0		2900	3100	01220005012
	25					200	1.200	15,0 - 19,5				01220005025
6,4	10	6,50	12,50	2,00	3,85	250	1.500	3,0 - 4,0		4900	5700	01220006410
	13					250	1.500	5,0 - 7,0				01220006413
	16					250	1.500	8,0 - 10,0				01220006416
	28					150	900	17,0 - 22,0				01220006428